CREEK ROCK



Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Creek Rock

Standard Colors: Apache Brown, Calico Sand, Palm Springs Blend, Southwest Blend or Any Custom Color

Grout Joint Width: Standard 1/2" Grout Joint or Drystacked (with some fill-in grout)

Grouting Options: Deep Raked or Drystacked

Grout Joint Color: Natural Grey, Natural Off-White, White or Complementary Color

Accessories: Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern: Blend the stone on the wall from several different boxes to ensure proper color and size variation.

See catalog photos for recommended installation pattern.

Grout Joints: When stacking Creek Rock, lay stones in a near-level position (10°-15° off-level maximum). Grouting may

be necessary.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we

suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar

on the back of each stone, which will prevent water pooling behind the stone after it's been installed.

Drystacked: A polymer modified mortar should be used for all drystacked applications.

Installation Info: Download Coronado's latest installation instructions at www.coronado.com for information on mortar and

installation recommendations.

Profile Properties

Size: Standard: 3" to 10" (nominal) Skippers: 1" to 2" in height and up to 6" in length (nominal).

The standard: 3" to 10" (nominal) Skippers: 1" to 2" in height and up to 6" in length (nominal).

The standard: 3" to 10" (nominal) Skippers: 1" to 2" in height and up to 6" in length (nominal).

The standard: 3" to 10" (nominal) Skippers: 1" to 2" in height and up to 6" in length (nominal).

Weight: 7 to 10 lbs. per square foot.

Packaging: Available in big boxes (100 sq ft Flats & 100 lft Corners) or Dura-Paks (12.5 sq ft Flats & 12.5 lft Corners).

When purchasing Creek Rock, coverage is based on installation with a 1/2" joint at the back of the stone.

Drystacked

CREEK ROCK



COLOR: PALM SPRINGS BLEND

1/2" Deep Raked White Grout Joint



CREEK ROCK

COLOR: APACHE BROWN