

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Pavilion Stone

- Standard Colors:** Pinecreek or Any Custom Color
- Grout Joint Width:** Drystack or 3/8" Grout Joint
- Grouting Options:** Deep Raked, Drystack, Shallow Brushed, Full Brushed or Full Smooth Tooled
- Grout Joint Color:** Natural Grey, Dark Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Stone should be installed in a horizontal ashlar pattern. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Avoid exceeding 2 medium in height.
- Horizontal Joints:** Avoid exceeding 6' to 8' in length.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Drystack:** A polymer modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 4" to 12" in height and 4" to 20" in length (nominal).
- Thickness:** 1/2" to 1"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (140 sq ft Flats & 100 lft Corners) or Dura-Paks (14 sq ft Flats & 13 lft Corners).
When purchasing Pavilion Stone, coverage is based on installation with tightly-fitted joints.

Drystack

