

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Valley Cobble

- Standard Colors:** Desert Sunset, Rosewood, Saratoga Springs, Wind River or Any Custom Color
- Grout Joint Width:** Standard ½" Average Grout Joint or varies from ¼" - 1" Average Grout Joint
- Grouting Options:** Deep Raked, Full Brushed, Full Smooth Tooled, Overgrout or Rough Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** To achieve the appearance of Valley Cobble as shown in the catalog, either the top or bottom of each stone **MUST** be installed on a level or near-level position. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation.
See catalog photos for recommended installation pattern.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Grout Joints:** A grout joint is recommended. Since the face of Valley Cobble Stone is slightly tapered, a full grout joint will appear about ¼" wider than a raked joint. Therefore, to achieve a ¾" average full grout joint, the stones should be installed with a ½" joint at the back of the stone. Valley Cobble stone does not lend itself to a drystack installation.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 2" to 12" in height and 4" to 24" in length (nominal).
- Thickness:** 1" to 1¾"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (120 sq ft Flats & 100 lft Corners) or Dura-Paks (15 sq ft Flats & 12 lft Corners).
When purchasing Valley Cobble, coverage is based on installation with a ½" joint at the back of the stone.

½" Full Brushed Grout Joint

