

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Canyon Cobble

- Standard Colors:** Wind River, Palazzo, Indian Springs. Custom colors may be available for an upcharge.
- Grout Joint Width:** Standard ½" Average Grout Joint or varies from ¼" to 1" Average Grout Joint
- Grouting Options:** Deep Raked, Full Brushed, Full Smooth Tooled, Overgrout or Rough Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** To achieve the appearance of Canyon Cobble as shown in the catalog, either the top or bottom of each stone MUST be installed on a level or near-level position. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation.
See catalog photos for recommended installation pattern.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Grout Joints:** A grout joint is recommended. Since the face of Canyon Cobble Stone is slightly tapered, a full grout joint will appear about ¼" wider than a raked joint. Therefore, to achieve a ¾" average full grout joint, the stones should be installed with a ½" joint at the back of the stone. Canyon Cobble stone does not lend itself to a drystack installation.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 2" to 10" in height and 4" to 24" in length. Corner returns range from 2" to 12" (nominal).
- Thickness:** 1" to 1¾" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (120 sq ft Flats & 100 lft Corners) or Dura-Paks (15 sq ft Flats & 12.5 lft Corners).
When purchasing Canyon Cobble, coverage is based on installation with a ½" joint at the back of the stone.
(Note: Square Footage and Linear Footage quantities may vary per region)

½" Deep Raked Grout Joint



CANYON COBBLE

COLOR: *WIND RIVER*

½" Deep Raked Grout Joint



CANYON COBBLE

COLOR: *INDIAN SPRINGS*