

## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to Canyon Ledge

- Standard Colors:** Cape Cod Grey, Brookside, Dakota Brown. Custom colors may be available for an upcharge.
- Grout Joint Width:** ½" Average Grout Joint, ¾" Average Grout Joint, 1" Average Grout Joint or Drystack
- Grouting Options:** Deep Raked, Drystack or Full Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

### Special Installation Notes

**Pattern:** To achieve the appearance of Canyon Ledge as shown in the catalog, either the top or bottom of each stone MUST be installed on a level or near-level position. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation.

**See catalog photos for recommended installation pattern.**

**Chalk Lines:** Should be used by installer to ensure a straight and level pattern.

**Grout Joints:** Stones need to be placed as close together as possible and grouted as deep as possible to achieve a ½" joint at the surface of the grout (this is due to the taper of the stone). In other words, the deeper you rake the grout into the joint, the smaller the grout joint appears. The fuller the grout joint, the wider the joint appears. Detailed grouting styles can be found in the Installation Section of the binder.

**Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

**Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.

**Drystack:** A polymer-modified mortar should be used for all drystack applications.

**Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

**Size:** Stone sizes range from 1" to 7" in height and up to 20" in length. Corner returns range from 3" to 10" (nominal).

**Thickness:** 1½" to 3" (nominal).

**Weight:** 7 to 10 lbs. per square foot.

**Packaging:** Available in big boxes (100 sq ft Flats or 100 ln ft Corners) or Dura-Paks (13 sq ft Flats or 10 ln ft Corners).  
**When purchasing Canyon Ledge, coverage is based on installation with a ½" joint at the back of the stone.**  
(Note: Square Footage and Linear Footage quantities may vary per region)

Drystack



CANYON LEDGE

COLOR: CAPE COD GREY

½" Deep Raked Grout Joint



CANYON LEDGE

COLOR: BROOKSIDE