

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Euro Villa®

- Standard Colors:** Champagne, Timberlake. Custom colors may be available for an upcharge.
- Grout Joint Width:** Standard ½" Average Grout Joint, 1" Average Grout Joint or 1½" Average Grout Joint
- Grouting Options:** Deep Raked, Full Brushed, Full Smooth Tooled, Overgrout or Rough Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Blend the stone on the wall from several different boxes to ensure proper color and size variation.
- Grout Joints:** The 1" average grout joint consist primarily of ¾" to 1" joints, not exceeding 1½" joints. Keep joints tighter in areas where three or more stones intersect because the joint will appear larger after grouting. A full grout joint is recommended. When the edge of the stone is tapered, stones should be placed closer together or about ½" to ¾" apart depending on the degree of taper. This will achieve a 1" joint at the surface of the stone. The deeper you rake the grout into the joint, the smaller the grout joint appears. The fuller the grout joint, the wider the joint appears.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 4" to 12" in diameter, averaging 8" (nominal).
- Thickness:** 1" to 1½"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (100 sq ft Flats or 100 ln ft Corners) or Dura-Paks (12.5 sq ft Flats or 12.5 ln ft Corners).
When purchasing Euro Villa®, coverage is based on installation with a ½" joint at the back of the stone.

¾" Full Brushed Grout Joint



EURO VILLA®

COLOR: CHAMPAGNE

Overgrout Grout Joint



EURO VILLA®

COLOR: TIMBERLAKE