

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Feathered Stone

- Standard Colors:** Orchard Hills. Custom colors may be available for an upcharge.
- Grout Joint Width:** Standard ½" Grout Joint, ¾" Grout Joint or Drystack
- Grouting Options:** Deep Raked, Drystack, Full Brushed or Full Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Stone should be installed in a horizontal, ashlar pattern, with joints broken up every 6' to 8'. Do not install vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. See brochure photos for recommended installation pattern. Detailed grouting styles can be found in the Installation Section of the binder.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Avoid exceeding 2 medium or 3 small stones in height.
- Horizontal Joints:** Avoid exceeding 6' to 8' in length. Detailed grouting styles can be found in the Installation Section of the binder.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** Due to the size of this profile, extra care should be taken to ensure a full coverage of mortar on the back of each piece, which will prevent water pooling behind the stone after it's been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 2" to 7" in height and 5" to 16" in length (nominal).
- Thickness:** ¾" to 1" (nominal)
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (120 sq ft Flats or 100 ln ft Corners) or Dura-Paks (15 sq ft Flats or 12.5 ln ft Corners).
When purchasing Feathered Stone, coverage is based on installation with a ½" joint at the back of the stone.

½" Deep Raked Grout Joint

