

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Sand Canyon Flagstone

Standard Colors: Desert Beige, Cream, Palomar Blend. Custom colors may be available for an upcharge.

Grout Joint Width: $\frac{1}{4}$ " Grout Joint (nominal)

Grouting Options: Full Smooth Tooled

Grout Joint Color: Natural Grey, Cream, Natural Off-White or Complementary Color

Accessories: Corners, Keystones, Trim Stones, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern: Blend the stone on the wall from several different boxes to ensure proper color. *Due to the large profile of the Sand Canyon Flagstone, Coronado recommends selecting an installer that has previous experience with precast or large tile installations. See catalog photos for recommended installation pattern.*

Chalk Lines: Should be used by installer to ensure a straight and level pattern.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.

Installation Info: Download Coronado's latest Classic Series installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

Size: Stone size is 16" in height and 30" in length. Corner returns are 3" for the short return and 15" for the long return (nominal).

Thickness: 1" (nominal).

Weight: 9 to 12 lbs. per square foot.

Packaging: Product sold by the piece.

$\frac{1}{4}$ " Full Smooth Tooled Grout Joint (nominal)



$\frac{1}{4}$ " Full Smooth Tooled Grout Joint (nominal)

