

## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to Lennox Stone

- Standard Colors:** Astoria White or Paint Grade  
**Grout Joint Width:** Drystack  
**Grouting Options:** Drystack  
**Grout Joint Color:** Color should be added to mortar to compliment stone color.

### Special Installation Notes

- Pattern:** Install stone in a versailles pattern. Lennox Stone is intended to be installed in interior applications only. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** **Small Pattern:** 4"x 4", 4"x 8", 8"x 8", 8"x 12"  
**Large Pattern:** 8"x 8", 8"x 16", 16"x 16", 16"x 24"
- Thickness:** 3/8" to 2" (random)
- Weight:** 12 lbs. per square foot (average)
- Packaging:** **Small Pattern:** Product sold in 4 ft increments.  
**Large Pattern:** Product sold in 16 ft increments.

Drystack

Random Pattern

