

## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to The Wave

- Standard Colors:** Product is Paint Grade (Designed to be painted after installation).
- Grout Joint Width:** 0" to 1/8" Grout Joint
- Grout Joint Color:** Grout joints should be filled and sanded, this will allow for a seamless look after painting the entire project.
- Accessories:** Inside and Outside Corners Available. If installing both inside and outside corners, please contact Coronado for additional information.

### Special Installation Notes

- Pattern:** Installing stones in a stacked bond pattern creates a seamless wave texture design. The Wave is intended to be installed in interior applications only. This product is produced using a gypsum based material.  
**For helpful installation hints please consult [www.CORONADO.com](http://www.CORONADO.com)**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Installation Info:** Download Coronado's latest Wave installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** 32" x 32", 32" x 64" panel (nominal)
- Thickness:** 1/2" to 1 1/2" (random)
- Weight:** 5 lbs. per square foot.
- Packaging:** Product sold by the piece.

