

6" SPLIT LIMESTONE



Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to 6" Split Limestone

- Standard Colors:** Cream, White, Summit Grey. Custom colors may be available for an upcharge.
- Grout Joint Width:** Drystacked or 3/8" Grout Joint
- Grouting Options:** Deep Raked, Drystacked, Shallow Brushed, Full Brushed or Full Smooth Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystacked:** A polymer-modified mortar should be used for all drystacked applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes 6" in height and up to 30" in length. Corner returns range from 6" to 10" (nominal).
- Thickness:** 1" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Product sold by the piece.

Drystacked



6" SPLIT LIMESTONE

COLOR: *WHITE*

Drystacked



6" SPLIT LIMESTONE

COLOR: *SUMMIT GREY*