

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Pro-Ledge®

- Standard Colors:** Huron, Black Forest, White, Oakbrook, Brookside, Alaskan Sunset. Custom colors may be available for an upcharge.
- Grout Joint Width:** Drystack
- Grouting Options:** Drystack
- Grout Joint Color:** Color should be added to mortar to compliment stone color.
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystack:** A polymer-modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** 4" panels in height and up to 20" in length. Corner returns range from 3¾" to 10" (nominal).
- Thickness:** 1" to 1½" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (120 sq ft Flats or 100 ln ft Corners) or Dura-Paks (15 sq ft Flats or 12 ln ft Corners). **When purchasing Pro-Ledge®, coverage is based on installation with tightly-fitted joints.**
(Note: Square Footage and Linear Footage quantities may vary per region)


Drystack



PRO-LEDGE®

COLOR: *HURON*

Drystack



PRO-LEDGE®

COLOR: *BLACK FOREST*