

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Amalfi Ledge

- Standard Colors:** Salerno, Pompeii, Winter Alps, Ravello. Custom colors may be available for an upcharge.
- Grout Joint Width:** Drystack
- Grouting Options:** Drystack
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)


Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Should be no higher than 8" on average or one large stone.
- Horizontal Joints:** Should not exceed 6' to 8'.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystack:** A polymer-modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Panel sizes are 2" and 6" in height and up to 24" in length. Corner returns range from 2" to 8" (nominal). Each stone within the panel is 2" in height and 3" to 10" in length (nominal).
- Thickness:** 1" to 1½" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (100 sq ft Flats or 100 ln ft Corners) or Dura-Paks (12 sq ft Flats or 12 ln ft Corners).
When purchasing Amalfi Ledge, coverage is based on installation with tightly-fitted joints.
(Note: Square Footage and Linear Footage quantities may vary per region)

Drystack



AMALFI LEDGE

COLOR: SALERNO

Drystack



AMALFI LEDGE

COLOR: POMPEII