

## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to Industrial Ledge

- Standard Colors:** Shale Grey, Blackened Oak, Oakbrook. Custom colors may be available for an upcharge.
- Grout Joint Width:** Drystack
- Grouting Options:** Drystack
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

### Special Installation Notes

- Pattern:** Blend the stone on the wall from several different boxes to ensure proper color and size variation.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Avoid exceeding 2 medium or 3 small stones in height.
- Horizontal Joints:** Avoid exceeding 6' to 8' in length.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Drystack:** A polymer modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** Stone sizes are from 2", 3", 4", 5" and 7" in height and range from 4" to 30" in length. Corner returns range from 1¾" to 10" (nominal).
- Thickness:** ¾" to 2" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (120 sq ft Flats or 120 ln ft Corners) or Dura-Paks (10 sq ft Flats or 12.5 ln ft Corners).  
**When purchasing Industrial Ledge, coverage is based on installation with tightly-fitted joints.**  
(Note: Square Footage and Linear Footage quantities may vary per region)
- Note:** The 30" long stones (1½" or 2" thick) stones can be tightly joined to create the illusion of a 60" piece.

Drystack



INDUSTRIAL LEDGE

COLOR: SHALE GREY

Drystack



INDUSTRIAL LEDGE COLOR: BLACKENED OAK