

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Refined WoodStone

- Standard Colors:** Blackened Oak, Antique White, Deadwood. Custom colors may be available for an upcharge.
- Grout Joint Width:** 1/8" Grout Joint or Drystack (nominal)
- Grouting Options:** Full Smooth Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** (See Accessories section of binder)

Special Installation Notes

- Pattern:** Blend the pieces on the wall from several different boxes to ensure proper color.
Due to the large profile of Refined WoodStone, Coronado recommends selecting an installer that has previous experience with precast or large tile installations.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** Due to the size of this profile, extra care should be taken to ensure a full coverage of mortar on the back of each piece, which will prevent water pooling behind the stone after it has been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Profile size is 6" in height and 36" in length (nominal).
- Thickness:** 1" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Product sold by the piece.

1/8" Full Smooth Tooled Grout Joint (nominal)



REFINED WOODSTONE COLOR: BLACKENED OAK

Drystack



REFINED WOODSTONE COLOR: ANTIQUE WHITE