

# 3" SPLIT LIMESTONE



## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to 3" Split Limestone

- Standard Colors:** Cream, Vista Pointe, Walnut, Summit Grey. Custom colors may be available for an upcharge.
- Premium Colors:** Black Forest, White.
- Grout Joint Width:** Drystack or 3/8" Grout Joint
- Grouting Options:** Deep Raked, Drystack, Shallow Brushed, Full Brushed or Full Smooth Tooled
- Grout Joint Color:** Color should be added to mortar to complement stone color.
- Accessories:** Complementary accessories are available (See [www.coronado.com/trimaccessories](http://www.coronado.com/trimaccessories))

### Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See [www.coronado.com](http://www.coronado.com) for photos of recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystack:** A polymer-modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** 3" in height and in the following lengths: 6", 10", 12", 14" and 18". Corner returns range from 3" to 10" (nominal).
- Thickness:** 1" - 1 3/4" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (120 sq ft Flats or 100 ln ft Corners) or Dura-Paks (12.5 sq ft Flats or 12.5 ln ft Corners). **When purchasing 3" Split Limestone, coverage is based on installation with tightly fitted joints.** (Note: Square Footage and Linear Footage quantities may vary per region)

Drystack



3" SPLIT LIMESTONE

COLOR: WHITE

Drystack



3" SPLIT LIMESTONE

COLOR: VISTA POINTE