

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Carolina Rubble

- Standard Colors:** Sandstone, Summer Cottage, Cathedral Grey. Custom colors may be available for an upcharge.
- Grout Joint Width:** Standard ½" or 1" for European look
- Grouting Options:** Deep Raked, Full Smooth Tooled or Full Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary accessories are available (See www.coronado.com/trimaccessories)

Special Installation Notes

- Pattern:** Stone should be installed in a horizontal ashlar pattern. To achieve additional angled transitions some trimming may be required. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation.
See www.coronado.com for photos of recommended installation pattern.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Avoid exceeding 2 medium or 3 small stones in height.
- Horizontal Joints:** Avoid exceeding 6' to 8' in length.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 2" to 10" in height and 4" to 16" in length. Corner returns range from 3" to 10" (nominal).
- Thickness:** 1¼" to 2¼" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (100 sq ft Flats or 85 ln ft Corners) or Dura-Paks (15 sq ft Flats or 11.5 ln ft Corners).
When purchasing Carolina Rubble, coverage is based on installation with a ½" joint at the back of the stone.
(Note: Square Footage and Linear Footage quantities may vary per region)

½" Shallow Brushed Grout Joint



CAROLINA RUBBLE

COLOR: SANDSTONE

½" Deep Raked Grout Joint



CAROLINA RUBBLE

COLOR: SUMMER COTTAGE