

## Installation Specifications

CSI – 3 Part Spec available at [www.CORONADO.com/ArchitecturalResources](http://www.CORONADO.com/ArchitecturalResources)

### Choices Specific to Old World Ledge

- Standard Colors:** Birch Grove, Vista Pointe, Huron, Etowah, Grey Quartzite, Chablis, Monarch, Cape Cod Grey, Antique Cream. Custom colors may be available for an upcharge.
- Grout Joint Width:** Standard  $\frac{3}{8}$ " to  $\frac{3}{4}$ " Average Grout Joint,  $\frac{1}{2}$ " to 1" Grout Joint or Drystack
- Grouting Options:** Deep Raked, Drystack, Full Brushed, Full Smooth Tooled or Rough Brushed
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary accessories are available (See [www.coronado.com/trimaccessories](http://www.coronado.com/trimaccessories))

### Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See [www.coronado.com](http://www.coronado.com) for photos of recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Should be no higher than 4" to 6" on average.
- Horizontal Joints:** Should not exceed 6' to 8'.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystack:** A polymer-modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** Stone sizes range from 1" to 5" in height and 4" to 16" in length. Corner returns range from 3" to 11" (nominal).
- Thickness:** 1" to  $1\frac{1}{2}$ " (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (120 sq ft Flats or 120 ln ft Corners) or Dura-Paks (15 sq ft Flats or 15 ln ft Corners). **When purchasing Old World Ledge, coverage is based on installation with a  $\frac{1}{2}$ " joint at the back of the stone.** (Note: Square Footage and Linear Footage quantities may vary per region)

Drystack



OLD WORLD LEDGE COLOR: BIRCH GROVE

Drystack



OLD WORLD LEDGE COLOR: VISTA POINTE