

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Urbana Smooth

- Standard Colors:** French White, Country Beige, Silver Ash. Custom colors may be available for an upcharge.
- Grout Joint Width:** ¼" Grout Joint (nominal)
- Grouting Options:** Full Smooth Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary accessories are available (See www.coronado.com/trimaccessories)

Special Installation Notes

- Pattern:** Blend the stone on the wall from several different boxes to ensure proper color. See www.coronado.com for photos of recommended installation pattern.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Installation Info:** Download Coronado's latest Classic Series installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone size is 7½" in height and 15½" in length (nominal). Corner returns are 3" for the short return and 11" for the long return (nominal).
- Thickness:** 1" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Product sold by the piece.

¼" Full Smooth Tooled Grout Joint (nominal)



URBANA SMOOTH COLOR: FRENCH WHITE

¼" Full Smooth Tooled Grout Joint (nominal)



URBANA SMOOTH COLOR: COUNTRY BEIGE