

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Weathered Edge

- Standard Colors:** Vista Pointe, Etowah, Northland. Custom colors may be available for an upcharge.
- Grout Joint Width:** ½" Grout Joint or Drystacke
- Grouting Options:** Deep Raked, Drystacke, Full Brushed or Full Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Complementary accessories are available (See www.coronado.com/trimaccessories)

Special Installation Notes

- Pattern:** Install stone in an ashlar pattern. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See www.coronado.com for photos of recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Should be no higher than 4" to 6" on average or one large stone.
- Horizontal Joints:** Should not exceed 6' to 8'.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystacke:** A polymer-modified mortar should be used for all drystacke applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** 1" to 6" in height and up to 20" in length. Corner returns range from 3" to 10" (nominal).
- Thickness:** 1" to 2½"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in Big Boxes (100 sq ft Flats or 100 ln ft Corners) or Dura-Paks (12.5 sq ft Flats or 12.5 ln ft Corners). **When purchasing Weathered Edge, coverage is based on installation with tightly-fitted joints.** (Note: Square Footage and Linear Footage quantities may vary per region)

Drystacke



WEATHERED EDGE COLOR: VISTA POINTE

Drystacke



WEATHERED EDGE COLOR: ETOWAH